

400 WATT SHORT THROW FOLLOWSPOT

400 WATT HTI FOLLOWSPOT SPECIFICATION
March 27, 2013

Part 1 GENERAL

1.01 RELATED DOCUMENTS:

Drawings and general provisions of Contract, including General and Supplementary Conditions, apply to work of this section

1.01 DESCRIPTION OF WORK:

- a. The Intent of this specification is to provide for the furnishing, testing and placing in operation, HTI Followspots. This equipment is designed to provide high quality lighting capabilities, with maximum ease of use and reliability for the wide variety of functions housed in these facilities.
- b. This Contractor shall provide all labor and materials and make all necessary arrangements, except as specifically noted herein, so that when the Contractor is finished, a fully working Followspot system will be turned over to the Owner. Any errors, omissions, or ambiguities are not to condition this requirement, but shall be brought to the attention of the Owner in their possible effect on the intent of this specification.

1.02 WORK EXCLUDED:

The following work is not included in this section:

- a. Receiving, uncrating, and placing in position of the Followspots;
- b. Electrical work, including the wiring of power receptacles to feed the Followspots.

1.03 QUALITY ASSURANCE:

- a. The equipment specified is the result of efforts to select equipment for reliability, ease of maintenance, and suitability for the Owner's purposes. Strict adherence to these specifications shall be required.
- b. Manufacturers:
 - 1. Provide products by the manufacturers indicated on the drawings and specifications. This apparatus is fully catalogued and described with complete technical data available from the manufacturers.
 - 2. Manufacturer approval shall not relieve the manufacturer from meeting the full requirements and intent of these specifications on each product specified
 - 3. Alternate Manufacturers or Products shall be acceptable only when they are submitted and approved at least ten days prior to the bid. Only equipment that in the opinion of the Owner equals or exceeds the features specified will be considered. Only followspots manufactured and assembled in the US are acceptable.
 - A. The Bidder shall provide working samples of proposed alternate equipment including lamping for any lighting fixtures, to be delivered to the premises designated, for examination by the Architects, Engineers, and such representatives as the Owner may direct. Handling shipping and delivery to, or removal from the site, of any sample required shall be at the cost of the Bidder.
 - B. The bidder shall further provide evidence of the alternate manufacturer's ability and plans to support the Followspots with parts and accessories.

4. Proposals which fail to address specification requirements or review comments will be rejected.
5. Equipment by a manufacturer which has not been approved prior to the bid shall not be acceptable.
- c. Warranties:
 1. The Followspots specified herein (except lamps) shall be warranted by the manufacturer to be free from defects of material or workmanship for a period of two year from the date of acceptance. During the period of this warranty, components which prove to be defective shall be repaired or replaced at no charge.
 2. This contractor shall coordinate all warranty repairs and replacements in cooperation with the owner.

1.04 OPERATION AND MAINTENANCE MANUALS:

When the installation is complete, the owner shall be supplied with:

1. One (1) set of **Operation and Maintenance Manuals**, including Safety and Maintenance information on all major units and principal components of the system.

1.05 PRODUCT STORAGE, DELIVERY AND HANDLING:

- a. Deliver Followspots securely wrapped in factory containers.
- b. Handle equipment and controls carefully to prevent breakage, denting and scoring of finish. Do not install damaged equipment and controls; replace and return damaged units to equipment manufacturer.

Part 2 PRODUCTS

2.01 FOLLOWSPOT

- a. The basis of this design shall be the 1266 Super Arc 400 follow spotlight, as manufactured by Lycian Stage Lighting of Sugar Loaf, NY.
- b. Physical
 1. The unit frame and enclosure shall be constructed of formed cold rolled steel and sturdy aluminum castings, free of burrs and protected by a gray and black powder coat finish.
 - A. The lamphouse shall include venting to direct heat out of the followspot lamphouse.
 - B. Handles shall be provided to facilitate smooth operation and to lift the unit.
 2. The unit shall be mounted on a stable, folding three-point stand with locking casters and leveling jacks.
 3. The Power Supply shall be integrated in the followspot.
 4. Weight of the followspot Head and Base shall not exceed 134 pounds.
 5. Length of head unit with color changing boomerang shall not exceed 32 1/2.”
- c. Controls
 1. The unit shall, as a minimum incorporate the following:
 - A. Bulb operation elapsed hour meter
 - B. Forced-air cooling by internally wired blowers and a fan

- C. ON/OFF ignition control (rocker switch located on body)
 - D. The luminaire shall incorporate an externally operable, continuously variable calibrated peak/flat field adjustment. The field diameter of the beam shall be continuously variable from the narrowest head spot to the widest flood by means of a nichrome steel iris which shall be operable by an external insulated, offset lever. Units that iris down without increase of light output shall not be acceptable..
 - E. HTI bulb mount, allowing unit to be safely wheeled with bulb in place
 - F. Mounted safety switch that turns the unit off should either the hood be removed or the lamp drawer opened.
2. The body of the unit shall, as minimum incorporate the following:
- A. Front and Rear Operated Fader Controls
 - B. Horizontal Trim Shutters
 - C. Spot edge focus adjusting knob
3. The unit shall house a seven color, self-canceling boomerang
- A. Boomerang shall be rigidly mounted to the body of the followspot
 - B. Front mounted boomerangs shall not be acceptable.
4. The stand/yoke shall incorporate:
- A. Horizontal Swing Control Lever
 - B. Vertical Tilt Control Lever
 - C. Height Adjustment
- d. Optical**
1. The unit's optical train shall consist of
- A. 400 watt HTI single ended lamp
 - B. Precision electroformed reflector
 - C. One coated optic and two optical quality glass lenses
 - D. Iris, horizontal trim shutters and dowser for beam shaping control
 - E. Internal seven color automatic, self-cancelling boomerang. Front mounted boomerangs are not acceptable. Sic color boomerangs are not acceptable.
2. The light color temperature shall be 5600° Kelvin ($\pm 200^\circ$ K.).
3. Reflector shall reflect 95% of visible light and absorb 90% of infrared light as heat
- e. Electrical**
1. HTI lamp system input shall be 100-120 V.AC, 60 Hertz, single phase, 15 ampere maximum and fused for 20 amperes. A universal ballast (UT) shall be available for international electrical requirements
2. Externally controllable power supply with meter to allow units to match output
3. 12' power cord terminated in a NEMA-5-15P connector
4. Only those lamps recommended by followspot manufacturer are acceptable.

f. Performance

1. Adjusted for flat field (approximately 70%) the unit shall produce 256 foot candles @ 100 feet. In small spot

2. The Field diameter at a 100 foot throw shall be as wide as 30 feet.

g. The following Optional accessories shall be available on and after time of purchase:

1. "Lo-Boy" stand

2. Hold down bolts

h. Furnish ____ () #1266 Super Arc 400 followspots, complete with all necessary accessories.

Part 3 EXECUTION

3.01 INSTALLATION:

a. This Contractor must examine areas and conditions under which followspots are to be installed and notify owner in writing of conditions detrimental to proper completion of the work. Do not proceed with the work until unsatisfactory conditions have been corrected in an acceptable manner.

b. Prior to energizing the followspots, all wiring shall be checked and tested by the owner to insure the system is free from grounds, opens and shorts.

3.02 SYSTEM COMMISSIONING:

a. After installation is complete, and before energizing the followspots, this contractor shall provide the services of a trained and authorized technician to commission the system as follows:

1. Safely lamp each followspot

2. Mechanically adjust the followspots to correct any misalignment caused by transportation or handling during the construction period.

3. Trim the light output of each followspot to maximize intensity with flat field.

b. This contractor shall provide training to instruct persons designated in the safe operation and maintenance of the followspot system.

c. The Contractor shall further submit certificates stating installed system is operating properly and complies with manufacturer's recommendations.

***** END OF SPECIFICATION *****