
## SUPER CLUBSPOT MODEL 1238

## **DIMENSIONS**



- A. Head length 353/4"
- B. Head height 16"
- \* C. Overall height with base 50"
- \* D. Height of pivot 40"
  - \*Additional upward height adjustment of 13"
- Width of base 27"
- Maximum width of head including controls - 14"

## **ARCHITECTS' & ENGINEERS' SPECIFICATIONS**

The luminaire shall be a 360 watt follow spotlight designed to accept only a FLE 360 watt 82 volt quartz MR16 lamp. A dual control variable focal length optical system shall be provided. As the beam diameter is reduced the intensity is increased. A nichrome heavy-duty iris and rear-controlled horizontal shutter shall also be included. The iris and shutters shall be fitted with insulated knobs. Only optical grade lenses shall be provided. Rapid lamp access shall be via a rear door. The lamp and color boomerang shall be cooled by a quietly operating fan. Power to the lamp shall be a heavy-duty provided by transformer; diodes shall not be acceptable. The unit also shall include an "on/off" rocker-type switch and a line cord terminated in a NEMA-5-15P (15 amp

parallel blade U-ground male.) The Super Clubspot shall contain a seven lever - six color plus dowser internal color boomerang. An extended front mounted boomerang shall not be acceptable. Current draw at 120 volts AC shall not exceed 4.5 amperes. The housing shall be constructed of cold rolled steel and extruded aluminium and finished with a powder coated finish. wrinkle Housing dimensions shall not exceed  $35^{3/4}$ "(L) x 16"(H) x 14"(W), including all controls. Net weight of the housing shall not exceed 49 lbs. The floor stand shall be of the three legged type, with locking casters, not to exceed 12 lbs. Photometric data shall conform to the table provided. The luminaire shall be a Lycian Stage Lighting Super Clubspot Model 1238.

## **ORDERING CODE**

<b>1238</b>	SUPER Clubspot
<b>1238/240</b>	SUPER Clubspot with 240 volt

PHOTOMETRICS						
THROW	40 ft.	60 ft.	80 ft.	100 ft.	125 ft.	
MINIMUM SPOT (w/IRIS)						
Footcandles	405	180	101	65	41	
Diameter	6"	10"	12"	15"	20"	
SMALL SPOT						
Footcandles	405	180	101	65	41	
Diameter	3.5'	5.5'	7.5'	9.2'	11.5'	
MAXIMUM FLOOD				•		
Footcandles	135	60	34	22	14	
Max. Diameter	9.2'	13.8'	18.4'	23'	28.75'	

