

**1000 WATT LED FOLLOWSPOT SPECIFICATION**

February 15, 2023

**Part 1 GENERAL**

**1.01 RELATED DOCUMENTS:**

Drawings and general provisions of Contract, including General and Supplementary Conditions, apply to work of this section

**DESCRIPTION OF WORK:**

The Intent of this specification is to provide for the furnishing, testing and placing in operation, LED Followspots. This equipment is designed to provide high quality lighting capabilities, with maximum ease of use and reliability for the wide variety of functions housed in these facilities.

This Contractor shall provide all labor and materials and make all necessary arrangements, except as specifically noted herein, so that when the Contractor is finished, a fully working Followspot system will be turned over to the Owner. Any errors, omissions, or ambiguities are not to condition this requirement, but shall be brought to the attention of the Owner and their possible effect on the intent of this specification.

**WORK EXCLUDED:**

The following work is not included in this section:

Receiving, unpacking, and placing in position of the Followspots;

Electrical work, including the wiring of power receptacles to feed the Followspots.

**QUALITY ASSURANCE:**

The equipment specified is the result of efforts to select equipment for reliability, ease of maintenance, and suitability for the Owner's purposes. Strict adherence to these specifications shall be required.

**Manufacturers:**

Provide products by the manufacturers indicated on the drawings and specifications. This apparatus is fully catalogued and described with complete technical data available from the manufacturers.

Manufacturer approval shall not relieve the manufacturer from meeting the full requirements and intent of these specifications on each product specified

Alternate Manufacturers or Products shall be acceptable only when they are submitted and approved at least ten days prior to the bid. Only equipment that in the opinion of the Owner equals or exceeds the features specified will be considered.

The Bidder shall provide working samples of proposed alternate equipment including lamping for any lighting fixtures, to be delivered to the premises designated, for examination by the Architects, Engineers, and such representatives as the owner may direct. Handling shipping and delivery to, or removal from the site, of any sample required shall be at the cost of the bidder.

The bidder shall further provide evidence of the alternate manufacturer's ability and plans to support the Followspots with parts and accessories.

Proposals which fail to address specification requirements or review comments will be rejected.

Equipment by a manufacturer which has not been approved prior to the bid shall not be acceptable.

Warranties:

The Followspots specified herein shall be warranted by the manufacturer to be free from defects of material or workmanship for a period of three year from the date of shipment. The LED itself shall be warranted for a period of 5 years. During the period of this warranty, components which prove to be defective shall be repaired or replaced at no charge.

This contractor shall coordinate all warranty repairs and replacements in cooperation with the owner.

OPERATION AND MAINTENANCE MANUALS:

When the installation is complete, the owner shall be supplied with:

Three (3) sets of **Operation and Maintenance Manuals**, including Safety and Maintenance information on all major units and principal components of the system.

PRODUCT STORAGE, DELIVERY AND HANDLING:

Deliver Followspots securely wrapped in factory containers.

Handle equipment and controls carefully to prevent breakage, denting and scoring of finish. Do not install damaged equipment and controls; replace and return damaged units to equipment manufacturer.

## **PRODUCTS**

FOLLOWSPOT

The basis of this design shall be the 1281 Super Star 1000 LED follow spotlight, as manufactured by Lycian Stage Lighting of Sugar Loaf, NY.

Physical

The unit frame and enclosure shall be constructed of formed cold rolled steel and sturdy aluminum castings, free of burrs and protected by a brown and black powder coat finish.

The lamphouse shall include venting to direct heat out of the followspot lamphouse.

Four handles shall be provided to facilitate smooth operation and to lift the unit.

The unit shall be mounted on a stable, folding four-point stand with locking casters and leveling jacks.

The Power Supply shall be integrated into the followspot.

## Long Throw Followspots

---

4. Weight of the followspot Head, Yoke and Base shall not exceed 183 pounds.
5. Length of head unit shall not exceed 57-1/2.”

### Controls

The Lamphouse shall, as a minimum incorporate the following:

- A Forced-air cooling by internally wired fan
- B ON/OFF ignition control
- C DMX Connection and control
- D Safety switch mounted to the lamphouse top

The body of the unit shall, as minimum incorporate the following:

Three Control Levers on top:

- Fader mechanism for smooth electronic dimming
- Horizontal chopping shutters
- Nichrome steel iris

Trombone style one handed zoom focus

Spot edge focus adjusting knob

The unit shall house a six color, self-canceling boomerang

Boomerang shall be rigidly mounted to the body of the followspot

Front mounted boomerangs shall not be acceptable. Color boomerangs that allow color frames to hang outside the main housing are not acceptable

The stand/yoke shall incorporate:

- Pan Control Lever
- Vertical Tilt Control Lever
- Height Adjustment

### Optical

The unit's optical train shall consist of

- 1000 Watt LED engine
- Variable focus lens system utilizing Optical-quality glass
- Iris, Choppers and dowser for beam shaping control
- Six color boomerang.
- Gobo slot

The zoom focus shall increase light intensity as it decreases the spot diameter.

A light color temperature of 5600° Kelvin ( $\pm 200^\circ$  K.)

### Electrical

LED system input shall be 100-250 V.AC, 50/60 Hertz, single phase

### Performance

## Long Throw Followspots

---

The unit shall produce 338-foot candles @ 100 feet in Spot focus

The Field diameter at a 100-foot throw shall be continuously adjustable from 24.5 feet in Flood focus to 8.9' small spot.

Field soft to hard edge focus shall be changed with an adjusting knob.

The following Optional accessories shall be available on and after time of purchase:

“Lo-Boy” stand

Gobo Holder

Underhanging Yoke

Furnish \_\_\_\_ ( ) #1281 Super Star 1000 Long Throw followspots, complete with all necessary accessories.

## **EXECUTION**

### INSTALLATION:

This Contractor must examine areas and conditions under which followspots are to be installed and notify owner in writing of conditions detrimental to proper completion of the work. Do not proceed with the work until unsatisfactory conditions have been corrected in an acceptable manner.

Prior to energizing the followspots, all wiring shall be checked and tested by the owner to ensure the system is free from opens and shorts.

### SYSTEM COMMISSIONING:

After installation is complete, and before energizing the followspots, this contractor shall provide the services of a trained and authorized technician to commission the system as follows:

Perform a final safety inspection to ensure controls operate correctly and safety is not compromised.

Mechanically adjust the followspots to correct any misalignment caused by transportation or handling during the construction period.

This contractor shall provide training to instruct persons designated in the safe operation and maintenance of the followspot system.

The Contractor shall further submit certificates stating installed system is operating properly and complies with manufacturer's recommendations.

**\*\*\* END OF SPECIFICATION \*\*\***